V2-GAN-A125

GATE VALVE, NON RISING STEM

PRODUCT SPECIFICATION SHEET



FEATURES

- Forged brass body
- Non Rising Stem
- Forged brass stem
- NPT / BSP threading

SPECIFICATIONS

Valve sizes:

 $\frac{1}{2}$ " to 2" (Threaded ends)

Nominal pressure:

200 psi from -20 °C to 170 °C (Water or non-caustic liquid saturated steam)

NO.	DESCRIPTION	MATERIAL	ASTM STANDARD					
1	Wheel Nut	Forged Brass	ASTM B124, C37700					
2	Name Plate	Aluminum Plate	Aluminum					
3	Handwheel	Gray Cast Iron	ASTM No. 208B					
4	Stem	Forged Brass	ASTM B124, C37700					
5	Pack Nut	Forged Brass	ASTM B124, C37700					
6	Gland	Forged Brass	ASTM B124, C37700					
7	Packing	Teflon	PTFE					
8	Thrust Sleeve	Forged Brass	ASTM B124, C37700					
9	Bonnet	Forged Brass	ASTM B124, C37700					
10	Disc	Forged Brass	ASTM B124, C37700					
11	Body	Forged Brass	ASTM B124, C37700					

DIMENSIONS in (mm)

Size	Part No. For NPT Threading	Part No. For BSP Threading	L	В	н	D
1⁄2"	V2-GAN-A125-A050	V2-GAN-A125-B015	46	12.85	75.8	55
3/4"	V2-GAN-A125-A075	V2-GAN-A125-B020	50	18.6	92	55
1"	V4-GAN-A125-A100	V4-GAN-A125-B025	55	23.5	100	72
1 ¼"	V4-GAN-A125-A125	V4-GAN-A125-B032	61	29.5	115.5	72
1 ½"	V4-GAN-A125-A150	V4-GAN-A125-B040	63.5	36.5	129	80
2"	V4-GAN-A125-A200	V4-GAN-A125-B050	72	49.5	153	100

